

Tychem® SL Level B Suit
Style No. 42122



Garment Description and Features:

Coverall, attached hood, elastic face, elastic wrists, front zipper closure, storm flap over zipper, attached boots

Fabric Description

Tychem® SL - a lightweight fabric made from DuPont™ Tyvek® laminated with a chemical resistant Dow Saranex® 23P film. It is a versatile fabric with trusted protection against a broad spectrum of chemicals.

Color: White

Seam Type

Bound - A clean finished binding which totally encloses the raw edges of two pieces of fabric. The binding is then sewn through all layers with a chain stitch.

TYCHEM®&NBSP;SL Technical Data

Properties	Test Method	Result Imp	Result Met
Basis Weight	ASTM D3776	3.5 oz/yd ²	
Breaking Strength - Grab	ASTM D5034	MD 47 lbs/ CD 50 lbs	
Mullen Burst	ASTM D3786	73 psi	
Tearing Strength - Tensile	ASTM D1777	MD 9 lbs/ CD 8 lbs	
Thickness	ASTM D1777	13 mils	

For Additional Information Contact:



184 Duke of Gloucester Street
Annapolis, Maryland 21401
United States of America

TEL: 1-410-295-0813

FAX: 1-410-295-0821

E-MAIL: Office@TradewaysUSA.com